



# Stainless steel range - Hinges

## Friction hinges

### Torque hinge B



Provides torque stability in both directions.

For pair using: Please use the same torque in both hinges.

When installing, ensure that both hinge axis are aligned.

Can not be used around water because not all parts are made of stainless steel.

Cycle life: 20,000 cycles.

Operating temperature: 0°C - 40°C.



Part number	Material	Finish	A	B	C	Torque	Note	Weight (g)
<b>NEW</b> 15-7-3574	430 stainless steel	polished	43	33	2.5	0.7 N.m	Type 1	31
<b>NEW</b> 15-7-3575	430 stainless steel	polished	43	33	2.5	0.7 N.m	Type 2	31
<b>NEW</b> 15-7-3576	430 stainless steel	polished	43	33	2.5	2.0 N.m	Type 1	32
<b>NEW</b> 15-7-3577	430 stainless steel	polished	43	33	2.5	2.0 N.m	Type 2	32
<b>NEW</b> 15-7-3562	430 stainless steel	polished	43	33	2.5	3.0 N.m	Type 1	32
<b>NEW</b> 15-7-3563	430 stainless steel	polished	43	33	2.5	3.0 N.m	Type 2	32
<b>NEW</b> 15-7-3564	430 stainless steel	polished	48	40	3	4.5 N.m	Type 1	67
<b>NEW</b> 15-7-3565	430 stainless steel	polished	48	40	3	4.5 N.m	Type 2	67

