

Stainless steel range - Accessories

Stainless steel slides

Full extension ball-bearing slide (3 pieces), soft-closing

LG = slide length.

K = travel length.

CN = load rating (kg/pair).

Soft-close slide.

The drawer can be detached by pushing the lever while pulling the drawer out.

Soft-closes at 20 mm distance from closed position (LG = 300-350 mm)

or 36 mm distance from closed position (LG = 400-700 mm).

The maximum width of the drawer is the slide length (LG) + 200 mm.



Produced mainly in stainless steel, for a complete description of the materials contact us.

Part number	Material	Finish	K	LG	Α	В	С	D	E	F	G	Н	CN	Weight (g)
21-7-3584	304 stainless steel	raw	265	300	145	-	-	-	-	-	-	174	16	390
21-7-3585	304 stainless steel	raw	340	350	151	-	-	-	-	-	-	224	16	465
21-7-3586	304 stainless steel	raw	400	400	167	-	-	-	96	-	-	256	20	535
21-7-3587	304 stainless steel	raw	450	450	119	215	-	-	128	-	-	306	30	605
21-7-3588	304 stainless steel	raw	500	500	119	279	-	-	96	160	-	344	35	680
21-7-3589	304 stainless steel	raw	550	550	119	215	311	-	96	160	-	394	35	730
21-7-3590	304 stainless steel	raw	600	600	119	247	375	-	128	192	-	444	35	830
21-7-3591	304 stainless steel	raw	650	650	119	215	311	407	128	224	416	494	35	905
21_7_3502	304 stainless steel	raw	700	700	110	215	3/13	/71	128	224	/8N	5//	35	980







