



FinAlu® continuous hinge



270° ALU ✓ RoHS

Continuous hinges in aluminium profile with a small pin diameter.

This nice design can be used in many applications (medical, electronic enclosures, food equipment, transportation...).

These hinges have the same dimensions as hinges used in the aircraft industry.



| Part number | Material | Finish | A | B | C | D | E | Pin material | Note | Weight (g) |
|---------------|-------------|-----------------|------|-------|-----|-----|------|-----------------|-----------|------------|
| 72-1-4243 | 6082 T5 alu | anodised | 915 | 31.75 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 150 |
| NS 72-1-4338 | 6082 T5 alu | blue anodised | 915 | 31.75 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 150 |
| NS 72-1-4339 | 6082 T5 alu | red anodised | 915 | 31.75 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 150 |
| NS 72-1-4340 | 6082 T5 alu | bronze anodised | 915 | 31.75 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 150 |
| NS 72-1-4341 | 6082 T5 alu | gold anodised | 915 | 31.75 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 150 |
| 72-1-4244 | 6082 T5 alu | raw | 1830 | 31.75 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 300 |
| NEW 72-1-4418 | 6082 T5 alu | anodised | 915 | 38.1 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 170 |
| NEW 72-1-4419 | 6082 T5 alu | raw | 1830 | 38.1 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 340 |
| 72-1-4245 | 6082 T5 alu | anodised | 915 | 44.45 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 190 |
| NS 72-1-4342 | 6082 T5 alu | blue anodised | 915 | 44.45 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 190 |
| NS 72-1-4343 | 6082 T5 alu | red anodised | 915 | 44.45 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 190 |
| NS 72-1-4344 | 6082 T5 alu | bronze anodised | 915 | 44.45 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 190 |
| NS 72-1-4345 | 6082 T5 alu | gold anodised | 915 | 44.45 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 190 |
| 72-1-4246 | 6082 T5 alu | raw | 1830 | 44.45 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 380 |
| 72-1-4247 | 6082 T5 alu | anodised | 915 | 63.5 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 250 |
| NS 72-1-4346 | 6082 T5 alu | blue anodised | 915 | 63.5 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 250 |
| NS 72-1-4347 | 6082 T5 alu | red anodised | 915 | 63.5 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 250 |
| NS 72-1-4348 | 6082 T5 alu | bronze anodised | 915 | 63.5 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 250 |
| NS 72-1-4349 | 6082 T5 alu | gold anodised | 915 | 63.5 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 250 |
| 72-1-4248 | 6082 T5 alu | raw | 1830 | 63.5 | 1.3 | 2.2 | 12.7 | stainless steel | undrilled | 500 |

