Bellows suction cup (oval)

https://www.schmalz.com/10.01.06.03201



SAOB 60x30 HT1-60 G3/8-AG

Part no.: 10.01.06.03201

Homepage > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Bellows Suction Cups (Oval) > Bellows Suction Cups SAOB HT1 (Oval, 1.5 Folds) > SAOB 60x30 HT1-60 G3/8-AG

Bellows suction cup (oval) for high dynamic on curved, oily surfaced workpieces




Dimensions (LxB): 60 x 30 mm

Suction cup material: High temp material HT1 Material hardness: 60 °Sh Nipple material: Aluminium Vacuum connection: G3/8-M

Number of folds: 1.5

Design Data



Attribute	Value
B1	31 mm
Bmax(S)	33 mm
Bs	30.6 mm
dn	5.2 mm
G1	G3/8"-M
Н	27.5 mm
L1	55.7 mm
LG1	7.4 mm
Lmax(S)	63 mm
Ls	60.6 mm
SW1	22 mm
Z	7 mm



Technical Data

Attribute	Value
Suction force	38 N
Pull-off force	69.5 N
Lateral force	80.1 N
Lateral force (oily surface)	40.5 N
Volume	10.5 cm ³
Curve radius (min) (convex)	18 mm
Internal hose diameter (recom.)	4 mm
Dimensions (LxB)	60 x 30 mm
Number of folds	1.5
Suction cup material	High temp material HT1
Material hardness	60 °Sh
Weight	30 g
Product family	SAOB

Note:

- Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a smooth, dry workpiece surface they do not include a safety factor
- Lateral force: The specified lateral forces are values measured at a vacuum of -0.6 bar with a dry or oily, smooth, flat workpiece surface. Depending on the workpiece surface and its quality, the actual values may deviate from these values
- Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m