

# Ejector module

## SEP HV 2 16 22 S

Part no.: 10.02.01.01410

<https://www.schmalz.com/10.02.01.01410>



Homepage > Vacuum Technology for Automation > Vacuum Components > Vacuum Generators > Ejector modules > Ejector Modules ecoPump


SEP > SEP HV 2 16 22 S

### Multistagenozzle as a cartridge



Shape: High vacuum  
Number of stages: 2  
Nozzle size: 1,6 mm  
Hole diameter: 22 mm  
Shape: With safety valve  
Degree of evacuation: 90 %  
Pressure range (operating pressure):  
2.0 ... 6.0 bar  
Pressure optimal: 4 bar  
Suction rate (max): 152.6 l/min  
Air consumption (during evac.):  
103 l/min

### Design Data



Attribute	Value
-----------	-------

D1	10.8 mm
----	---------

D2	21.8 mm
----	---------

L1	8 mm
----	------

L2	67.5 mm
----	---------

L3	92 mm
----	-------

### Technical Data

#### Contact to Schmalz

J. Schmalz GmbH | Johannes-Schmalz-Straße, 72293 Glatten, Deutschland | +49 7443 2403-102 | [customercenter@schmalz.de](mailto:customercenter@schmalz.de)

Attribute	Value
Weight	15.8 g
Ambient temperature	0 ... 60 °C
Int. hose diameter (recom.) comp.-air	6 mm
Int. hose diameter (recom.) vacuum side	12 mm
Pressure range (operating pressure)	2.0 ... 6.0 bar
Pressure range (operating pressure)	29.0 ... 87.0 psi
Pressure optimal	4 bar
Pressure optimal	58 psi
Noise level (free)	87 dB
Noise level (workp. gripped)	76 dB
Design	High vacuum
Suction rate (max)	9.39 m <sup>3</sup> /h
Suction rate (max)	152.6 l/min
Suction rate (max)	5.388 cfm
Air consumption (during evac.)	6.34 m <sup>3</sup> /h
Air consumption (during evac.)	103 l/min
Air consumption (during evac.)	3.637 cfm
Degree of evacuation	90 %
Number of stages	2
Nozzle size	1.6 mm
Hole diameter	22 mm

## Spare Parts

### Contact to Schmalz



**ERS-SET SEP-22 6xRUE-KLAP**

Part no. 10.02.01.01450

Set of spare parts  
for: Ejector module

Size: 22

contains: 6x Non-return flap

**Accessories**



**SHC 2 22**

Part no. 10.02.01.01512

Schmalz Holder Cap

Number of stages: 2

Hole diameter: 22 mm



**SD 29x70 SHC 22**

Part no. 10.02.01.01517

Silencer for vacuum generators

External diameter D: 29 mm

Length L: 70 mm

for: Schmalz Holder Cap

Size: 22



**SFE 22**

Part no. 10.02.01.01421

Schmalz Fixation Element

Hole diameter: 22 mm

Compressed-air connection: G1/4-F

Suction cup connection: G3/8-F

Vacuum connection: G1/4-F



**BEF-WIN 50x40x41 5 SFE-22**

Part no. 10.08.03.00315

Mounting bracket

Width B: 50 mm

Height H: 40 mm

Length L: 41 mm

Wall thickness s: 5 mm

for: Schmalz Fixation Element

Size: 22



**SET SFE 22**

Part no. 10.02.01.01577

Mounting set

for: Schmalz Fixation Element

Size: 22



**SEV G1/8-IG G1/4-AG**

Part no. 10.02.01.01471

Quick exhaust valve

Thread G1: G1/8-F

Thread G2: G1/4-M