

Vacuum pump

EVE-TR-X 140 AC3/S072


<https://www.schmalz.com/10.03.01.00241>



Part no.: 10.03.01.00241

Homepage > Vacuum Technology for Automation > Vacuum Components > Vacuum Generators > Vacuum Pumps > Dry-Running Vacuum Pumps
EVE-TR X > EVE-TR-X 140 AC3/S072

Oil-free pump with const. suct. rate robust, requ. little maintenance long service life, cont. operation



Current type: 3-phase AC
Noise level (50 Hz): 76 dB
Voltage (50 Hz): D230V/Y400V $\pm 10\%$
Voltage (60 Hz): D265V/Y460V $\pm 10\%$
Voltage (60 Hz-opt):
D230/Y400V $\pm 10\%$ (o. IE2)
Suction rate (50 Hz): 129 m³/h
Suction rate (60 Hz): 154 m³/h
Vacuum (50Hz): -900 mbar
Permission: IE2
Rated power (50 Hz): 4 kW
Rated power (60 Hz): 4.8 kW
Weight: 111 kg

Design Data



Attribute	Value
-----------	-------

B	470 mm
---	--------

B2	107.5 mm
----	----------

d	12 mm
---	-------

G3	G1-1/2"-F
----	-----------

G5	M8-F
----	------

H	336 mm
---	--------

L	873 mm
---	--------

L2	140 mm
----	--------

X1	398 mm
----	--------

Contact to Schmalz


J. Schmalz GmbH | Johannes-Schmalz-Straße, 72293 Glatten, Deutschland | +49 7443 2403-102 |
customercenter@schmalz.de

Attribute	Value
Y1	245 mm
Y2	122.5 mm

Technical Data

Attribute	Value
Suction rate (50 Hz)	129 m ³ /h
Suction rate (60 Hz)	154 m ³ /h
Voltage (50 Hz)	D230V/Y400V ±10%
Voltage (60 Hz)	D265V/Y460V ±10%
Rated power (50 Hz)	4 kW
Rated power (60 Hz)	4.8 kW
Noise level (50 Hz)	76 dB
Weight	111 kg
Protection	IP 55
Current type	AC3

Accessories



VBV -950...0 G1-1/4-AG EVE 80-140

Part no. 10.03.01.00153

Vacuum valve for limiting the maximum vacuum pressure

Vacuum range: -950 ... 0 mbar

Thread G1: G1-1/4"-M

Length L: 72 mm

for: Pump EVE

Size: 80-140

Contact to Schmalz

