

Vacuum pump

EVE-TR-X 140 AC3/S070 F


<https://www.schmalz.com/10.03.01.00284>



Part no.: 10.03.01.00284

Homepage > Vacuum Technology for Automation > Vacuum Components > Vacuum Generators > Vacuum Pumps > Dry-Running Vacuum Pumps
EVE-TR X > EVE-TR-X 140 AC3/S070 F

Oil-free pump with const. suct. rate robust, requ. little maintenance long service life, cont. operation



Current type: 3-phase AC
Noise level (50 Hz): 76 dB
Voltage (50 Hz):
D200V/Y350V $\pm 10\%$ (w/oIE2)
Voltage (60 Hz): D220V/Y380-400V $\pm 10\%$
Voltage (60 Hz-opt):
D200V/Y350V $\pm 10\%$ (w/oIE2)
with: Filter
Suction rate (50 Hz): 129 m³/h
Suction rate (60 Hz): 154 m³/h
Vacuum (50Hz): -800 mbar
Permission: IE2
Rated power (50 Hz): 4 kW
Rated power (60 Hz): 4.8 kW
Weight: 111 kg

Design Data



Attribute	Value
B	470 mm
B2	107.5 mm
d	12 mm
G2	G1-1/4"-F
G3	G1-1/2"-F
G5	M8-F
H	336 mm
H1	437 mm

Contact to Schmalz

J. Schmalz GmbH | Johannes-Schmalz-Straße, 72293 Glatten, Deutschland | +49 7443 2403-102 |
customercenter@schmalz.de

Attribute	Value
H2	75 mm
L	873 mm
L1	851 mm
L2	140 mm
X1	398 mm
Y1	245 mm
Y2	122.5 mm

Technical Data

Attribute	Value
Suction rate (50 Hz)	129 m ³ /h
Suction rate (60 Hz)	154 m ³ /h
Voltage (50 Hz)	D200V/Y350V ±10% (w/oIE2)
Voltage (60 Hz)	D220V/Y380-400V ±10%
Rated power (50 Hz)	4 kW
Rated power (60 Hz)	4.8 kW
Noise level (50 Hz)	76 dB
Weight	111 kg
Protection	IP 55
Current type	AC3

Accessories

Contact to Schmalz



FILT-EINS 3 98x70 PAP STF-1-1/4-IGN

Part no. 10.07.01.00018

Filter insert (round)

Filter pore size: 3 µm

External diameter D: 98 mm

Length L: 70 mm

Filter material: Paper

for: Filters STF

Size: 1-1/4-IGN